


SOLYX  
**SimGlas®**

## Reeded Glass ½" Window Film Specification Sheet



### Product Details

Reeded Glass ½" adhesive window film simulates real reeded glass. Bands are 1/2" wide and the reeded band direction runs vertically down the length of the roll. The reeded band height is determined by the length of the material ordered.

### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Specification

Product Code	SX-1254
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	68.5cm / 27"
Thickness	50 micron
Visible Light Transmission	61%
UV Rejection	43%
Total Solar Reflectance	8%
Total Solar Absorbance	15%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### INSTALLATION NOTE

This film has a horizontal, inherent, very fine pattern repeat every 13"/330mm.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Polyester

#### Adhesive

Clear, Pressure-sensitive

#### Release Liner

Silicone Coated

### Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)

Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)