

SOLYX  
**UltraCool®**

## 15% VLT Silver Solar Control Window Film Specification Sheet



### Product Details

15% VLT Silver Solar Control window film sets the industry standard as one of the most powerful and economical solar heat rejecting films available while maintaining minimal light reduction.

### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Specification

Product Code	UltraCool-S1560
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	76.2cm / 30"
Thickness	50 micron
Visible Light Transmission	25%
Visible Light Reflectance	55.9%
UV Transmission	<1%
Solar Absorption	36.8%
Solar Energy Rejected	78.3%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Metalised Polyester

#### Adhesive

Pressure-sensitive

#### Release Liner

Transparent Synthetic

### Contact Information

#### Surface Designs

Tel: +44 (0) 800 970 6366

Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)

Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)