

SOLYX®

Aurora Dichroic Window Film Specification Sheet



Product Details

Aurora Dichroic window film is a reflective, metal-free film made of multi-layered polyester for colour shifting special effects.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

Product Code	SX-3066
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	76.2cm / 30"
Thickness	38 micron
Visible Light Transmission	67%
UV Transmission	71%
Solar Energy Absorbed	22%
Visible Light Reflection	15%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

38 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Plottable Synthetic

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com