

SOLYX®

Charcoal Matte Window Film Specification Sheet



Product Details

Charcoal Matte is a smooth, charcoal tinted, translucent polyester film with a matte finish. This film obscures visibility while allowing good light transmission.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

Product Code	SXWF-CM
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	76.2cm / 30"
Thickness	50 micron
Visible Light Transmission	22%
UV Transmission	0%
IR Transmission	63%
Visible Light Reflection	22%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com