

## SOLYX®

# Clear Fine Brushed Window Film Specification Sheet



## **Product Details**

Clear Fine Brushed is a durable, high grade embossed brushed pattern vinyl film. This film is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

#### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

## **Specification**

Product Code	SXL-1017
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	76.2cm / 30"
Thickness	125 micron
Visible Light Transmission	39%
UV Transmission	48%
IR Transmission	52%
Visible Light Reflection	70%

## **Installation & Warranty**

#### **Installation**

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Construction**

## Face Film

125 micron Vinyl

#### **Adhesive**

Clear, Pressure-sensitive

### **Release Liner**

Silicone Coated

## **Contact Information**

#### **Surface Designs**

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com