

SOLYX  
**SimGlas®**

## Florentine Window Film Specification Sheet



### Product Details

Florentine window film is a fully removable and reusable static cling film ideal for obscuring daytime view and providing excellent shading with good lighting.

### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Specification

Product Code	SX-SC679
Film Type	Polypropylene
Adhesive Type	Static Cling
Usage	Interior
Available Roll Width(s)	60.95cm / 24"
Thickness	203 micron
Visible Light Transmission	65%
UV Transmission	1%
IR Transmission	75%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

203 micron Polypropylene

#### Adhesive

Static Cling

#### Release Liner

Transparent Synthetic

### Contact Information

#### Surface Designs

Tel: +44 (0) 800 970 6366

Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)

Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)