



Light Glare Control Window Film Specification Sheet



Product Details

Light Glare Control window film is a transparent, optically clear, UV stabilised, coloured, glare control polyester film with scratch resistant protective coating.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

Product Code	UltraGlare-G035
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	76.2cm / 30"
Thickness	50 micron
Visible Light Transmission	33%
Visible Light Reflectance	4%
UV Transmission	1%
Solar Absorption	40%
Solar Energy Rejected	35%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Non-Reflective Polyester

Adhesive

Pressure-sensitive

Release Liner

Transparent Synthetic

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com