

## SOLYX®

### Mosaic Window Film Specification Sheet



#### Product Details

Mosaic window film is a fully removable and reusable static cling film ideal for obscuring daytime view and providing excellent shading with good lighting.

#### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Specification

Product Code	SX-SC513
Film Type	Polypropylene
Adhesive Type	Static Cling
Usage	Interior
Available Roll Width(s)	88.9cm / 35"
Thickness	203 micron
Visible Light Transmission	65%
UV Transmission	1%
IR Transmission	75%

#### Installation & Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

##### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Construction

##### Face Film

203 micron Polypropylene

##### Adhesive

Static Cling

##### Release Liner

Transparent Synthetic

#### Contact Information

##### Surface Designs

Tel: +44 (0) 800 970 6366

Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)

Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)