



Prism Window Film Specification Sheet



Product Details

Prism window film is a fully removable and reusable static cling film ideal for obscuring daytime view and providing excellent shading with good lighting.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

| | |
|----------------------------|----------------|
| Product Code | SX-SC509 |
| Film Type | Polypropylene |
| Adhesive Type | Static Cling |
| Usage | Interior |
| Available Roll Width(s) | 90.1cm / 35.5" |
| Thickness | 203 micron |
| Visible Light Transmission | 65% |
| UV Transmission | 1% |
| IR Transmission | 75% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

203 micron Polypropylene

Adhesive

Static Cling

Release Liner

Transparent Synthetic

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com