

SOLYX SimGlas®

Reeded Glass 1/4" Window Film Specification Sheet



Product Details

Reeded Glass 1/4" adhesive window film simulates real reeded glass. Bands are 1/4" wide and the reeded band direction runs vertically down the length of the roll. The reeded band height is determined by the length of the material ordered.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

| | |
|----------------------------|--------------------|
| Product Code | SX-1262 |
| Film Type | Polyester |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Available Roll Width(s) | 68.5cm / 27" |
| Thickness | 50 micron |
| Visible Light Transmission | 61% |
| UV Rejection | 43% |
| Total Solar Reflectance | 8% |
| Total Solar Absorbance | 15% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

INSTALLATION NOTE

This film has a horizontal, inherent, very fine pattern repeat every 13"/330mm.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com