

SOLYX
SimGlas®

Rhombus Window Film Specification Sheet



Product Details

Rhombus window film is a clear translucent / transparent, high grade embossed film. This product is ideal for obscuring direct visibility while allowing excellent light transmission. protective backing.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

Product Code	SX-1730
Film Type	Polypropylene
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60.95cm / 24"
Thickness	100 micron
Visible Light Transmission	69%
UV Transmission	18%
IR Transmission	79%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

100 micron Polypropylene

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366
Email: sales@surfacedesigns.com
Web: www.surfacedesigns.com