

# SimGlas<sup>®</sup>

# Seeded Frost Window Film Specification Sheet



#### **Product Details**

Seeded Frost is a textured, transparent film made from durable polyester that provides a softened, distorted view. This film is 100% UV stabilised, will not discolour or shrink, and is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

## Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

# **Specification**

Product Code	SX-1278
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	68.5cm / 27"
Thickness	50 micron
Visible Light Transmission	90%
UV Transmission	1%
Solar Energy Absorbed	28%
Solar IR Energy Rejected	15%

# **Installation & Warranty**

#### **Installation**

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

# **Product Construction**

#### Face Film

50 micron Polyester

#### **Adhesive**

Clear, Pressure-sensitive

#### **Release Liner**

Transparent Synthetic

## **Contact Information**

# **Surface Designs**

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com