

SOLYX  
**SimGlas®**

## Solitude Window Film Specification Sheet



### Product Details

**Solitude** window film is a lightly textured, semi-transparent, polyester film that simulates glass and provides a distorted view and excellent light transmission.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

### Specification

Product Code	SX-1261
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	68.5cm / 27"
Thickness	50 micron
Visible Light Transmission	90%
UV Transmission	1%
Total Solar Reflectance	7%
Total Solar Absorbance	28%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Polyester

#### Adhesive

Clear, Pressure-sensitive

#### Release Liner

Transparent Synthetic

### Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)

Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)