

SOLYX
SimGlas®

Twilight Black Reeded Glass Window Film Specification Sheet



Product Details

Twilight Black Reeded Glass 1/2" adhesive window film simulates real reeded glass with a black tint. Bands are 1/2" wide and the reeded band direction runs vertically down the length of the roll. The reeded band height is determined by the length of the material ordered.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

Specification

Product Code	SX-1235
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	68.5cm / 27"
Thickness	50 micron
Visible Light Transmission	61%
UV Rejection	43%
Total Solar Reflectance	8%
Total Solar Absorbance	15%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

INSTALLATION NOTE

This film has a horizontal, inherent, very fine pattern repeat every 13"/330mm.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Contact Information

Surface Designs

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com