

## SOLYX®

### Web Effect Window Film Specification Sheet



#### Product Details

**Web Effect** is a durable, high grade embossed web pattern vinyl film. This film is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

#### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

**LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants** This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

#### Specification

Product Code	SXL-1022
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	59cm / 23.25"
Thickness	175 micron
Visible Light Transmission	65%
UV Transmission	2%
IR Transmission	52%

#### Installation & Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

##### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Construction

##### Face Film

175 micron Vinyl

##### Adhesive

Clear, Pressure-sensitive

##### Release Liner

Silicone Coated

#### Contact Information

##### Surface Designs

Tel: +44 (0) 800 970 6366  
Email: [sales@surfacedesigns.com](mailto:sales@surfacedesigns.com)  
Web: [www.surfacedesigns.com](http://www.surfacedesigns.com)