# SOLYX®

## Burnt Orange Organic Cotton Window Film Specification Sheet



## **Product Details**

Burnt Orange Organic Cotton is a orange, random, thin, vertical and horizontal line style simulating a woven cotton or muslin fabric. This film is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

#### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

LEED Credit EQ 4.1 Low Emitting Materials, Adhesives & Sealants This product has zero VOC content according to 40 CFR 59, Subpart D (EPA method 24).

## **Specification**

Product Code	SX-3174
Film Type	PET Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	74.5cm / 29"
Thickness	101 micron
Visible Light Transmission	34%
UV Transmission	1%
IR Transmission	71%

## **Installation & Warranty**

#### **Installation**

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Construction**

#### Face Film

101 micron PET Polyester

#### **Adhesive**

Clear, Pressure-sensitive

#### **Release Liner**

Silicone Coated

#### **Contact Information**

#### **Surface Designs**

Tel: +44 (0) 800 970 6366

Email: sales@surfacedesigns.com

Web: www.surfacedesigns.com